



SecureFolding security shutters



Robust folding security shutter made of impact-resistant aluminium

The topic of **security** and **protection** against burglary is becoming increasingly important. Be it at home in your own four walls, in commercial premises, business premises or remote holiday homes/apartments.

The innovative SECURE folding shutter was specially developed for the highest level of security requirements. Thanks to its ingenious design and extremely robust construction, it offers perfect protection against break-ins and vandalism.



UNIQUE DESIGN FEATURES

The SECURE horizontal folding shutter differs significantly from conventional roller and folding shutter designs. The armour does not fold from above, but from below on an angle end rail and is moved by a pushing chain drive.

FORCED DRIVE

The forced chain drive guarantees perfect functionality even under extreme conditions such as cold, snow and wetness. And this is true for both very small and very large shops.

DRIVE SYSTEMS

- \rightarrow Manual drive up to 4 m²
- \rightarrow 1 motor drive up to 9 m²
- \rightarrow 2 motors drive 9-12 m²



APARTMENT BUILDING, ST. GALLEN





BUSINESS PREMISES

SHOPS

IMPACT AND HAIL-RESISTANT

The anodised 1.5 – 2.5 mm thick aluminium and the slightly elongated shape of the shell offer uniquely high stability and impact resistance.

SUITABLE FOR NEW AND OLD BUILDINGS

The SECURE folding shutter does not require any special structural measures and is therefore suitable for both new and old buildings.

LOW INSTALLATION HEIGHT

The extremely low installation height enables installation without a lintel recess, or with just a very small one. Fits all standard lintel systems.

AUTOMATIC LOCKING

The SECURE folding shutter is automatically locked at any height thanks to its special design.





SINGLE-FAMILY HOUSES, VILLAS

RESTAURANTS, OUTDOOR BARS












Models




WIDE SLATS (BL) LINTEL WIDTH 135



LINTEL WIDTH 115



CURRED (BO)



NARROW SLATS (SL) LINTEL WIDTH 100



LIGHT AND AIR SLITS



Slits can be closed by a slider, in one or more slats.



Indirect ventilation and light slits between all slats. No slits are visible from the

outside.

UmbraTec GmbH

Schattentechnik Burgstrasse 87 CH-9000 St. Gallen/Switzerland

T +41712791181 info@umbratec.ch www.umbratec.ch

FEATURES

- → Solid aluminium shell with 1.2 1.5 mm wall thickness, hail-resistant
- → The armour can be automatically locked in any position via the side drive chain
- → Thanks to three different slat widths, any installation situation is possible
- → The end slat prevents any attack surface when closed
- → Protection against balls and stones that could destroy glass panes
- → High-quality materials
- → Protection class test EN 1627-1630 / ENV 13561



min. 50 cm max. 350 cm



min. 50 cm max. 350 cm

